

ADIBASIC 22

SPORT WOODEN FLOORING

FACT SHEET



System components:

01. Polyethylene sheath (nylon);
02. Elastic mat,
nominal thickness 18 mm;
03. Composite panels in plywood,
thickness 12 mm;
04. Parquet,
thickness 22 mm.

Total thickness: 52 mm.

Sports flooring/parquet **ADIBASIC 22**, is FIBA certified and is top level flooring with exceptional flexibility and a first-rate shock absorption. It is composed of:

01. **polyethylene sheath** with vapor barrier function extended to all the substrate surface (in order to avoid any humidity penetration);
02. **Elastic mat** can provide the right elasticity to the system, with shock absorption optimizing action and the subsequent release of energy. Nominal thickness 18 mm;
03. **Composite panels in plywood**, with not less five layers. They must be laid orthogonally to the direction of laying and staggered between them.
Nominal thickness: 12 mm.
04. **Parquet**, thickness 22 mm, with special joint on its long sides and heads, which ensures a perfect seal in tension and flatness of the paving and prevents the detachment of the boards from one another. The installation will involve fixing to the substructure with the planks already slotted to allow for the natural expansion of the wood.

Total thickness: 52 mm

Certifications:

- FIBA partner, 1 level
- certification EN 13501 fire reaction performed on the entire package class Cfl-s1
- certification EN 14904 indoor surfaces for multi-sports use
- CE marking
- Declaration of performance

Adisport srl reserves the right to modify the characteristics of the products at any time to improve their technical performance.